

1

Overview

- Air Safe Hitches (5th Wheel, Gooseneck, and Receiver)
- o "True Air" Makes The Difference
- Hitches totally ride on the air bags (no hinges except the Class 3 Rec)
- Air Safe Hitches delivers the ultimate in safety.

Features & Benefits

- **Safety** With Air Ride Hitches only 10% of the trailer inertia transfers compared to 100% using a hard connection hitch giving you ultimate control.
- Ultimate Control The tow vehicle and trailer independently giving you greater control and added safety, virtually eliminating all sway. Greatly increased braking control since all the weight on the tow vehicle and trailer is distributed evenly giving you increased positive contact when braking and maneuvering.

3

Features & Benefits

- Saves You Money Reduce trailer and content fatigue. Metal fatigue caused by traditional towing results in your trailer and its contents taking a beating. Air Hitch products increase life and help hold value.
- Arrive Alive Reduce driver fatigue to help ensure everyone (family, friends, pets, horses, and livestock) arrive alive.

Features & Benefits

- Safeguards Against Uncontrollable Road Conditions -Bumps, potholes, expansion joints, curves, hills, and other drivers can be a hazard. Air Hitch keeps you under control when confronted with these conditions.
- Saves Gas and Tire Wear The 90% smoother ride allows you to glide instead of bounce increasing gas mileage and tire wear.

5

Types of Trailers

- Horse Trailers
- Concession Trailers
- 5th Wheel Trailers
- Travel Trailers
- Cargo Trailers
- Race Car Trailers
- Boat Trailers
- Government Trailers
- Buses & Large Motor Homes Towing Trailers

5th Wheel Installation

- Standard Rails
- Underbed adapters
 - o Ford (All years and models use the same Ford adapter)
 - o Dodge (All years and models use the same Dodge adapter)
 - o GMC (2018-2019 use one GMC version, 2020 and up use another GMC version)

7

Receiver Installation

- o Shaft Sizes (2", 2 1/2" and 3")
- Shaft length
 - Standard shaft the hole from the middle of pin to the back of the hitch is 4"
 - Extended shaft the hole from the middle of pin to the back of the hitch is 6"
- Brackets Available
 - Ball Mount
 - Standard for Class 4-6
 - o 6" drop for Class 4-6
 - Heavy duty for Class 7-8
 - o 4" drop for Heavy duty for Class 7-8
 - O Adjustable Ball Mount (Just pull pin to raise or lower)
 - Pintle (We do not carry but the bolt hole patterns is the same as our hitches)
 - Weight Distribution

Gooseneck Installation o 4" Round o 4" Square o Extended 4" round (4" extended coupler) o Extended 4" square (4" extended coupler)

9

Availability

- o All Hitches are normally in stock
- o Ship within 3 business days of order
- o 5th Wheel and Gooseneck ship Freight
- o Receiver ship UPS

